



POLIMASTER[®]
Radiation Detection Technologies



X-RAY AND GAMMA RADIATION PERSONAL DOSIMETER **PM1610B**

PM1610 series of electronic personal dosimeters (EPDs) are intended for extended measurement of the **personal dose equivalent** and **personal dose equivalent rate**. The dosimeters are suitable for multiple applications providing the measurement of **continuous** and **pulsed X-ray and gamma radiation** in the wide energy range. PM1610 has unique features for operation in workplaces requiring the use of personal protective equipment or a harsh environment, including a shockproof rubberized case, a high contrast display with a fluorescent backlight, and two big buttons for easy use even while wearing protective gloves.

PM1610B model has an extended dose measurement range **up to 20 Sv** and **improved accuracy** of the dose rate measurement. Instead of a rechargeable battery, this model is powered by AAA (LR03) batteries which are easy to replace, affordable and safe to handle.

Applications

- First responders
- Industrial facilities
- Police and security
- Emergency services
- Nuclear power plants
- Healthcare professionals
- Customs and border control
- Anyone working under the risk of X-ray and gamma radiation exposure

Features

- Small and lightweight
- Shockproof hermetic case
- USB communication with PC
- Audible, visual and vibration alarms
- Simple navigation with two large buttons
- Measurement of pulsed photon radiation
- Wide dose and dose rate measurement ranges
- Extended energy range: from 20 keV to 10 MeV
- Easily replaceable long-life AAA battery: at least 480 hours



SPECIFICATIONS

Detector	Geiger-Mueller tube		
Dose rate measurement range	0.1 μ Sv/h to 10 Sv/h		
Dose rate measurement accuracy	$\pm(10+0.0015/\dot{H}+0.0015\cdot\dot{H}) \%$, where \dot{H} is the measured dose rate value in mSv/h		
Dose measurement range	0.05 μ Sv to 20 Sv		
– continuous photon radiation	0.05 μ Sv to 20 Sv		
– pulsed photon radiation	10 μ Sv to 20 Sv		
Dose measurement accuracy	$\pm 20 \%$		
Energy range	20 keV to 10 MeV		
Energy response relative to 0.662 MeV (¹³⁷Cs)	–60 % (20 keV to 33 keV)		
	–40 % (33 keV to 48 keV)		
	$\pm 30 \%$ (48 keV to 3 MeV)		
	$\pm 50 \%$ (3 MeV to 10 MeV)		
Minimum pulse duration of pulsed X-ray radiation	1 ms		
Memory	7500 events	Ingress protection	IP65
Alarms	visual, audible, vibration	Drop test	1.5 m
Communication	USB	Dimensions	$\leq 71 \times 59 \times 20$ mm
Power supply	AAA (LR03) battery; external via USB	Weight	≤ 90 g
Battery lifetime (average dose rate < 0.3 μ Sv/h, active alarms < 20 s / 24 h)	≥ 480 hours	Operating conditions	
		– ambient temperature	–20 °C to 50 °C
		– atmospheric pressure	84 kPa to 106.7 kPa
		– relative humidity	up to 98 % at 35 °C



Holder with a clip for secure fastening



Compatible with PM530 Automated Personal Dosimetry System



Direct micro-USB connection for easy data transfer

Polimaster Inc.
44873 Falcon Place, Suite 128
Sterling,
VA 20166, USA
phone: +1 703 525 5075
fax: +1 703 525 5079
info@polimaster.us

Polimaster Europe UAB
Ezero str. 4, Dėdizialio k.,
Nemezio sen., LT-13264,
Vilnius district, Lithuania
phone: +370 5 210 2323
fax: +370 5 210 2324
info@polimaster.com

Polimaster Japan Co., Ltd.
AUBE2 5-177 Kuratsuki,
Kanazawa, Ishikawa Prefecture
920-8203 Japan
phone: + 81 076 201 8623
fax: + 81 076 201 8624
pacific@polimaster.jp